



GANZ KK

GANZ SITE DISTRIBUTION BOARD

GENERAL FEATURES:

- ▶ Rugged Metal Frame Construction: Provides weather protection and ensures easy, convenient transport across work sites.
- ▶ Impact-Resistant Enclosure: Manufactured from high-strength, glass-fiber reinforced plastic.
- ▶ Ingress Protection: Enclosure rated IP65, socket outlets rated IP44.
- ▶ Safety & Access Control: Lockable main switch and lockable hinged transparent door for protective devices (MCBs/RCD).
- ▶ Circuit Protection: Overload, short-circuit, and residual current protection for all single-phase and three-phase outlets.
- ▶ Daisy-Chaining Capability: Allows loop-in / loop-through connection of additional site distribution units.
- ▶ Rated Insulation Voltage: 500 V
- ▶ Applicable Standards: MSZ EN 61439-4, MSZ 2364-704



Technical Parameter	GFB-40	GFB-63
Rated Current (I _n)	40 A	63 A
Overall Dimensions (H × W × D)	870 × 550 × 800 mm	
Main Switch	KKEV2-40-9021	KKEV2-63-9021
Residual Current Device (RCD / RCCB)	40A, 4P, 30 mA	63A, 4P, 30 mA
Miniature Circuit Breakers (MCBs)	3 × 1P C16A 1 × 3P C16A 1 × 3P C32A	
Socket Outlets	6 × 16 A single-phase sockets (230V) 1 × 16 A three-phase 5-pin socket (400V) 1 × 32 A three-phase 5-pin socket (400V)	

*Mindent IS
kapcsolunk...*



GANZ Switchgear and Appliance Manufacturing Ltd.

Address: H-1101 Budapest, Kőbányai út 41/c

Phone: +36 (1) 261 1115

Web: www.ganzkk.hu

E-mail: ganzzkk@ganzkk.hu